

PRODUCT SPECIFICATIONS

FINISHED DIMENSIONS

Adjustments are taken from ordered dimensions and may vary slightly.

Inside (IB) Mount	
Headrail width	- 3/4"
Blind width	- 1/2"
Blind height	ordered height
Valance	- 1/8"
Outside (OB) Mount	
Headrail width	- 1/4"
Blind width	ordered width
Blind height	ordered height
Valance	+ 1"
2 on 1 Headrail	
Gap between panels	Approx. 1/4" - 1/2"

FINISHED DIMENSIONS		
	Inside Mount	Outside Mount
Headrail	-1/2"	-1/2"
Blind Width	-1/2"	0"
Valance	-1/8"	+1"
<i>Do NOT make any deductions from your measurements</i>		

MOUNTING REQUIREMENTS


Use a metal tape measure for all measurements.

Inside (IB) Mount	
Minimum mounting depth: 2"	1-1/8"
Minimum mounting depth: 2-1/2"	1-1/4"
Minimum mounting depth, flush mount - 2" Slat:	3-1/2"
Minimum mounting depth, flush mount - 2-1/2" Slat:	3-3/4"
Outside (OB) Mount	
Minimum flat vertical surface:	1-3/4"


VALANCE ORDERING	
Outside Mount	1" Added to valance, measured inside returns
Inside Mount	-1/8" (no returns)
Max Un-Spliced	102"
Max Spliced	168"
NOTE: Valances are cut to measure inside miter to ensure the most accurate fit when installed over the headrail or window frame	

STANDARD RETURNS	
Inside Mount	1/2"
Outside Mount	3"


2-1/2" CRESCENT VALANCE



Mitered Corner



Corner Cap



Valance Clip

- Height: 2-1/2" Depth: 3/8"
- Standard with blind
- Returns are available with miter cuts that attach with hidden connectors or straight cuts that attach with visible corner caps
- Attaches with hidden, adjustable valance clip

