

## SIZE SPECIFICATIONS

### FINISHED DIMENSIONS

Adjustments are taken from ordered dimensions and may vary slightly.

| Inside (IB) Mount                      |                     |
|----------------------------------------|---------------------|
| Headrail width <sup>1</sup>            | - 3/4"              |
| Blind width                            | - 1/2"              |
| Blind height                           | ordered height      |
| Valance                                | - 1/8"              |
| Outside (OB) Mount                     |                     |
| Headrail width <sup>1</sup>            | - 1/4"              |
| Blind width                            | ordered width       |
| Blind height                           | ordered height      |
| Valance (measured from inside corners) | + 1"                |
| 2 on 1 Headrail                        |                     |
| Gap between panels                     | Approx. 1/4" - 1/2" |

### MOUNTING REQUIREMENTS

Use a metal tape measure for all measurements.

| Inside (IB) Mount                             |        |
|-----------------------------------------------|--------|
| Minimum mounting depth - 2"                   | 1-1/8" |
| Minimum mounting depth - 2-3/8"               | 1-1/4" |
| Minimum mounting depth, flush mount - 2":     | 3-1/2" |
| Minimum mounting depth, flush mount - 2-3/8": | 3-3/4" |
| Outside (OB) Mount                            |        |
| Minimum flat vertical surface                 | 1-3/4" |

#### FOOTNOTE

- 1 The headrail width has a 1/4" deduction on outside mounts and 3/4" deduction on inside mounts to accommodate the installation brackets.