

Cellular Shades

SPECIFICATIONS

Cordless (3/8") Single Cellular Light Filtering		
Minimum & Maximum Widths & Lengths:		
	Minimum	Maximum
Width	18 ³ / ₈ " W	72" W
Length	24" L	72" L
Head Rail Dimensions:		
Depth	1 ⁵ / ₈ " deep	
Height	1" high	
Minimum Depth Requirements:		
Inside Mount	1 ³ / ₁₆ "	
Inside Flush Mount	2"	
Standard Factory Deductions:		
Inside Mount	3/8" (3/16" per side)	
Outside Mount	0"	

Cordless (3/8") Single Cellular TDBU Light Filtering		
Minimum & Maximum Widths & Lengths:		
	Minimum	Maximum
Width	18 ³ / ₈ " W	72" W
Length	24" L	84" L
Head Rail Dimensions:		
Depth	1 ⁷ / ₈ " deep	
Height	1 ⁷ / ₈ " high	
Minimum Depth Requirements:		
Inside Mount	1 ³ / ₈ "	
Inside Flush Mount	2 ¹ / ₈ "	
Standard Factory Deductions:		
Inside Mount	3/ ₈ " (3/ ₁₆ " per side)	
Outside Mount	0"	

Cordless (3/8") Double Cellular Light Filtering		
Minimum & Maximum Widths & Lengths:		
	Minimum	Maximum
Width	18" W	72" W
Length	24" L	84" L
Head Rail Dimensions:		
Depth	1 ⁷ / ₈ " deep	
Height	1 ⁷ / ₈ " high	
Minimum Depth Requirements:		
Inside Mount	1 ³ / ₈ "	
Inside Flush Mount	2 ¹ / ₈ "	
Standard Factory Deductions:		
Inside Mount	3/8" (3/16" per side)	
Outside Mount	0"	

Cordless (5/8") Single Cellular Black Out		
Minimum & Maximum Widths & Lengths:		
	Minimum	Maximum
Width	19" W	* 72" W
Length	24" L	84" L
Head Rail Dimensions:		
Depth	1 ⁷ / ₈ " deep	
Height	1 ⁷ / ₈ " high	
Minimum Depth Requirements:		
Inside Mount	1 ³ / ₈ "	
Inside Flush Mount	2 ¹ / ₈ "	
Standard Factory Deductions:		
Inside Mount	3/ ₈ " (3/ ₁₆ " per side)	
Outside Mount	0"	

* Connector device option available for extra wide widths (72"-144¼")

Cordless (5/8") Single Cellular TDBU Black Out		
Minimum & Maximum Widths & Lengths:		
	Minimum	Maximum
Width	19" W	72" W
Length	24" L	84" L
Head Rail Dimensions:		
Depth	1 ⁷ / ₈ " deep	
Height	1 ⁷ / ₈ " high	
Minimum Depth Requirements:		
Inside Mount	1 ³ / ₈ "	
Inside Flush Mount	2 ¹ / ₈ "	
Standard Factory Deductions:		
Inside Mount	3/ ₈ " (3/ ₁₆ " per side)	
Outside Mount	0"	

Cordless (5/8") Single Cellular Day & Night		
Minimum & Maximum Widths & Lengths:		
	Minimum	Maximum
Width	18" W	72" W
Length	24" L	84" L
Head Rail Dimensions:		
Depth	1 ⁷ / ₈ " deep	
Height	1 ⁷ / ₈ " high	
Minimum Depth Requirements:		
Inside Mount	1 ³ / ₈ "	
Inside Flush Mount	2 ¹ / ₈ "	
Standard Factory Deductions:		
Inside Mount	3/ ₈ " (3/ ₁₆ " per side)	
Outside Mount	0"	