

Eclipse/Nightfall Roller Shades

Black Out

FEATURES & BENEFITS

SPECIFICATIONS									
Lift Options:									
Cordless Spring Motor			Acculift w/ Fabric Insert Cassette		CCO		Motorized Motorwand	Motorized No Cassette/ Open Roll	Motorized w/ Fabric Insert Cassette
convolute paper tube*			aluminum tube		1" steel tube plastic beaded chain		aluminum tube	aluminum tube	aluminum tube
Minimum & Maximum Widths & Lengths:									
	min	max	min	max	min	max	min	max	
Width	15"W	84"W	24"W	72"W	15"W	103"W	20"W	96"W	
Length	24"L	84"L	24"L	72"L	24"L	120"L	24"L	120"L	
Cassette Valance Dimensions:									
Depth	N/A		3 ¹ / ₂ " deep						
Height	N/A		3" high						
Minimum Depth Requirements (for mounting brackets):									
	open roll/no cassette		Acculift		with cassette valance				
Inside Mount	2 ³ / ₈ "		2 ⁵ / ₈ "		2 ⁵ / ₈ "				
Inside Flush Mount	3"		3 ¹ / ₂ "		3 ¹ / ₂ "				
Outside Mount	0"		0"		0"				
* Note: Minimum depth for flush inside mount of standard roller shades (i.e. without a cassette valance) varies with each fabric thickness and depends on how far the shade is raised. The measurement listed is the maximum depth, fully raised, made of the thickest fabric.									
Standard Factory Deductions									
	open roll/no cassette		Acculift		with cassette valance				
Inside Mount	1 ¹ / ₈ "		1 ¹ / ₈ "		1 ¹ / ₈ "				
Outside Mount	0"		0"		0"				